

ABC-600

High voltage dual channel cycling station



Key Features:

- 99% Power Factor
- Energy Returned to the Grid at 92+% Efficiency
- Dual Independently Controlled Channels
- Analog Control Signal
- Automatic Shutdown on Loss of Power (Anti-Islanding)
- Independent Channel Interlock
- Load Disconnect Protection (camlock model only)
- Easy Front Panel Connections
- Emergency Stop Button
- Flexible DC Supply or Load Capabilities
- Fully Programmable Computer Control
- Multiple Control Interfaces/Options: Manual, Remote Operating System (ROS) Software, LabView, CAN and 3rd Party Control Software
- Remote Voltage Sense
- Bi-Directional Load Capability

Designed for higher voltage testing

Webasto Charging Systems, Inc. ABC-600 is a high voltage cycling station that was originally developed to meet specific customer requirements. This system is ideal for testing hybrid vehicles and high voltage drivetrains, motors and energy storage devices. The ABC-600 offers power up to 150kW, with a voltage range of 8 to 600VDC and a current range of ± 600 ADC.

Technical specifications

	ABC-600
Input voltage options	3 Phase, 380, 440 and 480 VAC
Currencydraw	254, 218 and 200 A respectively
Frequency	60 Hz (50 Hz available)
Isolation transformer	Internal transformer
Power factor	> 99%
Harmonic distortion	< 3% THD; IEEE 519 Compliant
Multiple user interfaces	Manual; Remote Operation System (ROS); DCOM Driver for LabVIEW; C++ and Visual Basic; CAN
Current ripple - independent & parallel mode	< 65mArms and 130mArms, respectively
Current ripple - max ripple from load	< 15Arms
Operating environment - temperature	32 - 95°F (0 - 35°C)
Operating environment - humidity	5-90% non-condensing
Weight	2-power stages 4,055 lbs. (1,839 kg)
Dimensions (L x W x H)	73 x 37 x 76.5 in. (185 x 94 x 194 cm)

Operating range

Configuration	Voltage (Vdc)	Current (Adc)	Power (kW)
Independent	+8 to +600	-300 to +300	-150 to +150
Parallel	+8 to +600	-600 to +600	-150 to +150

Accuracy & resolution

Measurement	Accuracy (±)	Resolution
Voltage	250mV or 0.15% of the output voltage	50mV
Current independent (2 channels)	250mA or 0.25% of the reading	20mA
Current external parallel (1 channels)	450mA or 0.35% of the reading	40mA



PTS Brochure



evtestsystems.com

Webasto Thermo & Comfort
North America, Inc.

15083 North Road
Fenton, Michigan 48430
USA

Toll Free: 800-860-7866
Phone: 810-593-6000

evtestsystems.com