

## For an ideal climate in your RV

You found your perfect spot for the night or the next few days. Now it's time to relax. When it's really hot outside it's great to have that air-conditioned retreat where you can cool down. Good to know that your home on wheels always awaits you with the ideal comfort temperature!

### For an ideal climate in your RV

The Cool Top Trail air conditioners are suitable for use in parked motorhomes and caravans of up to 10 m length. With their generously sized heat exchangers they have a high efficiency and high performance. Their reliability and high cooling capacity has already been proven in very hot Australian summers with up to 50 °C outside temperatures. The units come with heat pump function as a standard which is also very powerful, working in cold outside temperatures of as low as -5 °C.

### High performance at low noise

Very low noise levels allow you to rest and relax inside the vehicle and not disturb your neighbors in the RV campsite. The use of high-quality components ensures a long lifetime with a minimum expenditure on maintenance. Made from UV stabilized polypropylene, the housing of the units is robust but still lightweight. The units can be operated with an easy to handle remote control which allows the user to access all air conditioner functions from the comfort of the dining area, seat or bed. Besides cooling and heating the units include various extra features such as dehumidification, timer and sleep function.



## Cool Top Trail 20G/24G/28G/28V/34G/36V/35G

Rooftop air-conditioning systems



The Cool Top Trail series offers a range of specifications tailored to different vehicle sizes.



More information about  
Cool Top Trail



Contact details

Hotline:  
+49 (0)395 5592 229

E-Mail:  
kundencenter@webasto.com

[webasto.com](https://www.webasto.com)

06/25 • Errors and omissions excepted • © Webasto 2025

recommended by  
**Marcel Schrötter**  
Motorbike Racer  
Superbike World Championship

## Cool Top Trail 20G / 24G / 28G / 28V



Cool Top Trail 20G / 24G

Cool Top Trail 28G / 28V

### The advantages of the Cool Top Trail 20G / 24G / 28G

- **Now with environmental friendly refrigerant gas R32** with very low GWP value of only 675
- Powerful units with high cooling and heating capacity
- The weight of the Cool Top Trail 20G and 24G has been reduced by 0,5 kg
- Robust, lightweight and low noise
- Wide operating range from -5 to 50 °C
- Low profile and compact design
- Easy installation
- Suitable for use in motorhomes & caravans of **up to 8 m length**

### The advantages of the Cool Top Trail 34G / 35G NEW

- **Now with environmental friendly refrigerant gas R32** with very low GWP value of only 675
- Powerful units with highest cooling and heating capacity
- Robust, lightweight and low noise
- Wide operating range from -5 to 50 °C
- Low profile and compact design
- Easy installation
- Suitable for use in motorhomes & caravans **from 8 m to 10 m length**

## Cool Top Trail 34G / 36V / 35G



Cool Top Trail 34G / 36V

Cool Top Trail 35G

### The advantages of the Cool Top Trail 28V / 36V

- **Variable speed compressor technology** provides low noise levels, particularly when unit is reducing compressor and blower speed
- Powerful cooling and heating capacity with less energy consumption, smooth start-up without starting peak
- Possibility to reduce electrical power consumption with the new ECO1 and ECO2 functions when needed, enabling to use the unit also in some campsites when less power from the grid is available
- Low profile and compact design
- Turbo mode to provide fast cool down or heat up of vehicle
- Suitable for use in parked motorhomes, camper vans and caravans of **up to 10 m length**

## Cool Top Trail 20G / 24G / 28G / 28V

Technical specifications:

Cool Top Trail	20G	24G	28G	28V
Cooling capacity (W)	2.000	2.400	2.800	2.800
Heating capacity (W)	2.000	2.400	2.600	2.600
Nominal voltage / frequency (V) / (Hz)	230~ / 50			
Rated current (cooling mode) (A)	3.0	4.2	5.0	4.8
Rated current (heating mode) (A)	2.6	3.8	4.8	4.8
Operating temperature range (°C)	-5 to 50			
Roof thickness (mm)	25 to 85		25 to 70	
Roof cut-out (mm)	400 x 400 (360 x 360 with optional adaptor frame)			
Dimensions outdoor unit (mm)	1002 x 566 x 215		855 x 657 x 215	
Dimensions indoor unit (mm)	557 x 536 x 43		575 x 556 x 49	
Weight total (kg)	30.3	31.3	36	34.9

## Cool Top Trail 34G / 36V / 35G

Technical specifications:

Cool Top Trail	34G	36V	35G
Cooling capacity (W)	3.400	3.600	3.500
Heating capacity (W)	3.200	3.300	3.500
Nominal voltage / frequency (V) / (Hz)	230~ / 50		
Rated current (cooling mode) (A)	5.8	6.4	5.2
Rated current (heating mode) (A)	5.4	6.2	5.1
Operating temperature range (°C)	-5 to 50		
Roof thickness (mm)	25 to 70		
Roof cut-out (mm)	400 x 400 (360 x 360 with optional adaptor frame)		
Dimensions outdoor unit (mm)	1.122 x 850 x 223		998 x 680 x 340
Dimensions indoor unit (mm)	575 x 556 x 49		557 x 536 x 43
Weight total (kg)	48.5	41.9	38.3