Webasto
Feel the Drive

Air Top Go 20

Go for affordable and reliable comfort

The Air Top Go 20 is the smart choice for customers seeking Webasto quality at an attractive value.
Built on the proven Air Top Pro platform, Air Top Go 20 combines the same compact dimensions and robust hardware with a streamlined feature set focused on essential functionality. Delivering heating output from 1.0 to 1.5 kW and up to 2.0 kW in boost mode for up to two hours, it ensures rapid vehicle warm-up and dependable comfort in everyday operation.

Optimized for efficiency, the Air Top Go 20 offers low fuel consumption and long service life thanks to its brushless EC drive. Communication is based on the proven W-Bus interface, ensuring compatibility with the complete range of Webasto control elements for straightforward installation and operation.

Compatible with both Diesel and HVO fuel, the Air Top Go 20 provides a reliable and cost-effective heating solution for a wide range of vehicle applications. The air heater can be installed both inside the vehicle and externally on the chassis.

Key benefits at a glance:

- Heating output from 1.0 - 2.0 kW
- Demand-based heat emission through stepless, temperature-controlled heating power regulation
- Operation up to 2,500 meters altitude
- High efficiency with reduced power consumption
- Suitable for continuous heating operation
- Cyber security acc. ISO/SAE 21434 and functional safety acc. ISO 26262

Truck | Light vehicles | Recreational vehicles | Off-Highway

Technical specifications

	Air Top Go 20	
ECE approval mark & CE conformity	ECE R10, ECE R122, CE	
Heat output, control range (kW) / Boost	1.0 - 1.5 / 2.0	
Boost duration (h)	2	
Rated voltage (V)	12	24
Fuels	Diesel DIN EN 590 Paraffinic fuel (HVO/GTL) DIN EN 15940	
Fuel consumption (ml/h)	140 - 280	
Electrical power consumption (W)	max. 12	
Operating temperature range (°C)	-40 to +40	
Altitude functionality	Operation up to 2,500 m altitude	
Dimensions L x W x H (mm)	321 x 127 x 124	
Weight (kg)	2.95	
Mechanical interface	Identical to Air Top 2000 STC	
Communication interface	W-Bus	

Scope of delivery & installation kit

The proven and known components and accessories will be offered in SODs and KITs

Recommended controls*

ThermoConnect

- Control of the heater via smartphone
- Status display on smartphone and pushbutton in vehicle
- Multiple switch-on times per day, programmable 7 days in advance
- Intelligent heating time management for selected departure time

UniControl

- Status display via multicolored LED
- 3 selectable switch-on times per day, programmable 7 days in advance
- Suitable for ADR
- Installation in universal mounting slot

Telestart

- Select heating time over distance
- Up to 1,000 meters range
- Multi-colored LED for status report

MultiControl

- Status display via multicolored LED
- 3 selectable switch-on times per day, programmable 7 days in advance
- Universal installation without modifications to dashboard

Digital rotary selector

- Status display via LED
- Stepless adjustment of heating power
- Suitable for ADR
- Installed in dash (requires drilling)

* Please see our product catalog for further controls

08/26 • Errors and omissions excepted • Printed in Germany • © Webasto 2026