

MultiControl

Intuitive dashboard control panel for all Webasto parking heaters



The MultiControl sets standards in terms of its modern design and user-friendliness. The dashboard control panel is ideal for all those who wish to have pre-set vehicle temperature at scheduled times.

Operate your Webasto parking heater conveniently and intuitively with the state-of-the art MultiControl control panel. Thanks to large TFT display, multifunctional button and self-explanatory user interface access to functions has never been easier.

MultiControl allows quick selection of comfort heating levels and operation time. Eco, Normal or Boost functions are meant to deliver exceptional energy-savings for Air Top Evo heaters or – if necessary – very quick heat-up times. The availability of the comfort functions depends on the installed heater, though.

With the built-in timer function you can pre-program start times for your heater, 7 days in advance. Simple menu navigation allows a quick creation of individual pre-selection times and heating/ventilation functions.

During hot summer days an air ventilation function can be switched on as well, in order to equalize high air temperature inside the vehicle with outside ambient temperature.

In addition to the TFT display, the operating states are indicated by a multicolored LED on the instant start button, so that the current status is always visible at a glance. White for standby,

Key benefits at a glance:

- Intuitive user interface for convenient operation
- Quick heating comfort level selection for Air Top Evo series
- 7-day timer function
- Ventilation function to equalize summer heat in the vehicle
- Status indication via multicolored LED
- "Instant start" button function for quick heater or ventilation launch
- Quick and easy dashboard installation thanks to special holding frame
- High altitude functionality of up to 3,000 m optional for Recreational vehicles

green for heating, blue for ventilation and red for error.

Additionally, the ON/OFF button can work as an instant start button, allowing heating or ventilation at the touch of a button.

The dashboard control panel is also available as SmartControl with ADR function for use in hazardous goods transporters.

Further features:

- Diagnostic interface for W-Bus heaters and the Webasto Thermo Test Software
- Selection of the continuous heating is enabled for RV and Marine specific heaters



Car



Truck

Light
Vehicles

Bus

Recreational
Vehicle

Marine



Off-Highway

Special
Vehicles

Technical specifications

	MultiControl
Operating time	10 – 120 minutes 5 min. increments continuous heating function (RV only)
Power supply (V DC)	12/24
Power consumption, stand-by (mA)	0.5
Operating temperature range (°C)	-20 to +70
Connection type	Analogue Switch Output/W-Bus
Dimensions (L x W x H) (mm)	67.5 x 9.5 x 48
Weight (g)	41
IP protection class	IP5k4k
ECE approval number	E1 10R – 047319
CE Declaration of Conformity	2014/30/EU 2011/65/EU for further information see declaration of conformity

Available variants:

- MultiControl Car: Passenger cars
- MultiControl HD: Commercial Vehicles
- MultiControl Mar RV TT: RV/Marine Coolant Heaters
- MultiControl Mar RV ATE: RV/Marine Air Heaters

Scope of delivery:

- MultiControl
- Adhesive pads
- QuickStart Guide

Supported Webasto heaters:

- Thermo Top Evo 4 / 5 / 5+
- Thermo Pro 50 Eco
- Thermo Pro 90
- Thermo Top Pro 120 / 150
- Air Top 2000 STC
- Air Top Evo 40/55