

Telestart T100 HTM

Intelligent remote control for parking heaters



Telestart T100 HTM is a wireless, intuitive and ergonomic remote control for Webasto parking heaters. It has been specifically developed for customers with high comfort demand. The T100 HTM extends basic ON / OFF function known from other remote controls with further functionalities, such as intelligent timer, LCD display, feedback and temperature sensor functions.

Built-in LCD display indicates current interior temperature at all times. Several parking heater functions can be monitored via specified display pictograms, thus providing the user a statusreport about the vehicle and the heater.

The Heating Time Management System (HTM) calculates heating time based on three factors: Pre-set departure time, pre-set heating comfort level and current interior temperature. This function comes handy during fluctuating weather conditions and avoids unnecessary long pre-heating cycles during warmer temperatures or far too cold interior temperature after unpredictably frosty nights.

Thanks to its compact size the T100 HTM can always stay on a keychain with the car keys, in case the heater needs to be switched ON / OFF manually, and it works from up to 1,000 meters distance.

Key benefits at a glance:

- Check interior temperature and parking heater settings conveniently with built-in LCD display
- Intelligent Heating Time Management (HTM) pre-heats the car for you automatically
- Control your parking heater wirelessly from up to 1,000 meters distance
- Always in your pocket thanks to compact size
- Chose between up to five heating comfort levels
- Select heating or summer ventilation modes
- Adjust heating or ventilation time between 10 and 120 minutes
- Connect up to four transmitters to one car



Car



Light vehicles



Recreational vehicles



Marine

Technical specifications

	Transmitter	Receiver
Operating time	10 – 120 minutes	
Operating distance (m)	1,000	
Radio frequency (MHz)	868.3 (proprietary)	
Power supply	Battery 28L 6 V	12 V DC
Operating temperature range (°C)	0 to +50	-40 to +85
Dimensions (L x W x H) (mm)	70 x 37 x 18	85 x 65 x 16
Weight (g)	45	71
IP protection class	IP 54	IP 40
Connection type	-	Analog Switch Output / WBus
ECE approval number	E1 10R – 047488	
CE declaration of conformity	2014/53/EU for further information see declaration of conformity	

Scope of delivery:

- Transmitter Telestart T100 HTM
- Receiver Telestart T100
- Wiring harness
- Window antenna
- Temperature sensor
- Mounting bracket for receiver
- Battery 28L 6 V
- QuickStart Guide

Supported Webasto heaters:

- Thermo Top Evo 4 / 5 / 5+
- Thermo Pro 90 (12 V variant only)
- Thermo Top Pro 120 / 150 (12 V variant only)

Accessories:

- Toggle ON / OFF button for dashboard installation



Contact details

webasto.com